


SOCKET SD 035







Connection: 3 x pressure clamps for stranded and rigid wire 0.5 - 2.5mm²
Mounting: clip for 35mm DIN rail, EN 60715
Casing: plastic according to UL94 V-0, light grey variable
Fitting position: variable
Operating temperature: -45 bis +70 °C (-49 bis +158 °F)
Storage temperature: max. 90% RH (non-condensing)
Fuse: Ø 5 x 20mm
Protection type/Protection class: IP20 / I (earthed)
Weight: approx. 0,2kg
Dimensions: 92 x 62 x 48mm



Approbation: **corresp. RoHS,**
 EAC (SD035-D/D-O),
 UL File No. E222026 (SD035-USA/USA-O)

Customs tariff number: 85 36 90 10



Article name	Order no.	Socket	Operating voltage	Nominal current
SD035-D	103170	Germany/Russia with fuse	250 VAC	6,3 A
SD035-D-O	100941	Germany/Russia without fuse	250 VAC	16 A
SD035-AU/CN-O	100667	Australia/China without fuse	240 VAC	10 A
SD035-BRA-O	102360	Brazil without fuse	250 VAC	10 A
SD035-CH	103167	Switzerland with fuse	250 VAC	6,3 A
SD035-CH-O	100835	Switzerland without fuse	250 VAC	10 A
SD035-F	103173	F/PL/CZ/SK with fuse	250 VAC	6,3 A
SD035-F-O	101028	F/PL/CZ/SK without fuse	250 VAC	16 A
SD035-GB	103176	UK/Ireland with fuse	250 VAC	6,3 A
SD035-GB-O	101043	UK/Ireland without fuse	250 VAC	13 A
SD035-I	101923	Italy with fuse	250 VAC	6,3 A
SD035-I-O	101087	Italy without fuse	250 VAC	16 A
SD035-USA	103179	USA/Canada with fuse	125 VAC	6,3 A
SD035-USA-O	101108	USA/Canada without fuse	125 VAC	15 A

04.11.15

Richter Elektrotechnik GmbH & Co.KG

Nisterberger Weg 14
 Tel.: 027 43-9 1066-0
 www.richter-elektrotechnik.de

57520 Friedewald
 Fax: 027 43-9 1066-23
 info@richter-elektrotechnik.de